

EXTRA LOW PROFILE SCISSOR LIFT AUXILIARY LIFT 400V 5T ON-GROUND

Reference : PE 6250T



Item name	EXTRA LOW PROFILE SCISSOR LIFT AUXILIARY LIFT 400V 5T ON-GROUND
Bar code	3701555318080
Text	<p>Particularly suitable for technical inspections, geometries and repairs For installation on light and heavy-duty vehicles. Work comfort: quick and easy vehicle mounting on the extra-low 140mm bridge. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize position. Auxiliary lift capacity 4T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for enhanced durability. Pneumatically locked swing plates. Supplied with 2 swivel plates. Equipped with rails for optional lifting crossbar. PE 7100</p>
Product highlight	Low ground clearance: 140mm
Specifications	<p>Features :</p> <ul style="list-style-type: none">- lifting height: 140-1850mm- track width/length: 655/5200mm- total length with access ramps: 6600mm- system synchronization: photo cell- control panel- drive power: 3kw- drive voltage: (3 phases + Neutral) 400V/50Hz

- air supply required 6-8 bar.
- oscillating plates pneumatic locking
- 2 extra-flat turntables included
- epoxy paint
- emergency lowering system in case of power failure
- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period

2 years

Power

3000W

Voltage

400V

Length (mm)

5,200 mm

Width

2,190 mm

Product weight (kg)

2,689 kg

Max. height

1,850 mm

Min. height

140 mm

Maximum load (T)

5 T

Tariff code

Tariff Equipment (TE)

Composition of nomenclature

1 x PE 6250T-1 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-GROUND 1/5

1 x PE 6250T-2 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-GROUND 2/5

1 x PE 6250T-3 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-GROUND 3/5

1 x PE 6250T-4 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-GROUND 4/5

1 x PE 6250T-5 - EXTRA LOW PROFILE SCISSOR LIFT AUX 400V 5T ON-GROUND 5/5

4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

Warranty Procedure INTERVENTION

Customer benefit

Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required

YES

Circuit breaker/Cable section

16A D / 5x2.5mm²

on-ground/in-ground on-ground

Soil quality

>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)