

## Extra low profile scissor lift auxiliary lift 400V 5T on-ground

Reference : PE 6250T



<b>Item name</b>	Extra low profile scissor lift auxiliary lift 400V 5T on-ground
<b>Bar code</b>	3701555318080
<b>Text</b>	<p>Particularly suitable for technical inspections, geometries and repairs Free-standing for passenger cars and light commercial vehicles. Work comfort: quick and easy vehicle mounting on the extra-low 140mm lift. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize position. Auxiliary lift capacity 4T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for enhanced durability. Pneumatically locked swing plates. Supplied with 2 swivel plates. Equipped with rails for optional lifting crossbar. PE 7100</p>
<b>Product highlight</b>	Low ground clearance: 140mm
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 140-1850mm</li><li>- track width/length: 655/5200mm</li><li>- total length with access ramps: 6600mm</li><li>- system synchronization: photo cell</li><li>- control panel</li><li>- drive power: 3kw</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- air supply required 6-8 bar.</li></ul>

- oscillating plates pneumatic locking
- 2 extra-flat turntables included
- Epoxy paint
- emergency lowering system in case of power failure
- intermediate stop 20 cm above ground for user safety and anti-crushing audible signal

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

**Warranty period** 2 years

**Power** 3000W

**Voltage** 400V

**Length (mm)** 5,200 mm

**Width** 2,190 mm

**Product weight (kg)** 2,689 kg

**Max. height** 1,850 mm

**Min. height** 140 mm

**Maximum load (T)** 5 T

**Tariff code** Tariff Equipment (TE)

**Composition of nomenclature** 1 x PE 6250T-1 - Extra low profile scissor lift aux 400V 5T on-ground 1/5  
 1 x PE 6250T-2 - Extra low profile scissor lift aux 400V 5T on-ground 2/5  
 1 x PE 6250T-3 - Extra low profile scissor lift aux 400V 5T on-ground 3/5  
 1 x PE 6250T-4 - Extra low profile scissor lift aux 400V 5T on-ground 4/5  
 1 x PE 6250T-5 - Extra low profile scissor lift aux 400V 5T on-ground 5/5  
 4 x [SA 3012 - Hv46 hydraulic oil 5l](#)

**Warranty Procedure** INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Pneumatic power supply required** YES

**Circuit breaker/Cable section** 16A D / 5x2.5mm<sup>2</sup>

**on-ground/in-ground** on-ground

**Soil quality** >20cm Béton C20/25

**2**  
WARRANTY

  
**400V**



TE

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)