Extra-low pofile 400V 5T scissor lift, free-standing, with 4T auxiliary lifting

Reference : PE 6250T




Item name	Extra-low pofile 400V 5T scissor lift, free-standing, with 4T auxiliary lifting
Bar code	3701555318080
Text	5T free-standing scissor lift, particularly suited for technical inspections, diagnostics, and repairs on LVs and commercial vehicles Easy access: extra-low design at just 140 mm, allowing the vehicle to be driven onto the lift quickly and easily Maximum safety: mechanical rack-and-pinion locking on the main and auxiliary scissor arms, ensuring perfect stabilization in the working position 4T auxiliary lifting, equipped with 2 galvanized extensions to facilitate underbody support Enhanced durability: auxiliary lifting system cylinder with chrome plating for improved long-term durability Easier wheel alignment thanks to oscillating plates with pneumatic locking Ready to use: comes with 2 swivel platforms. Versatile: integrated rails allow for the use of an optional lifting crossbar (PE 7100).
Product highlight	Extra-thin: only 140 mm high
Specifications	Specifications: - Lifting height: 140–1,850 mm - Width/length of bearing rails: 655/5,200 mm - Total length with access ramps: 6,600 mm - Photocell synchronization system - Control panel - Drive power: 3 kW

	- Drive voltage: (3-phase + neutral) 400 V/50 Hz - Required air supply: 6–8 bar - Pneumatically locked oscillating plates - 2 low pofile turntables included - Epoxy paint finish - Emergency descent system in case of power failure - Intermediate stop 20 cm above the ground for user safety and an anti-crushing audible alarm
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	5,200 mm
Width	2,190 mm
Product weight (kg)	2,689 kg
Max. height	1,850 mm
Min. height	140 mm
Maximum load (T)	5 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6250T-1 - Extra low profile scissor lift aux 400V 5T on-ground 1/5 1 x PE 6250T-2 - Extra low profile scissor lift aux 400V 5T on-ground 2/5 1 x PE 6250T-3 - Extra low profile scissor lift aux 400V 5T on-ground 3/5 1 x PE 6250T-4 - Extra low profile scissor lift aux 400V 5T on-ground 4/5 1 x PE 6250T-5 - Extra low profile scissor lift aux 400V 5T on-ground 5/5 4 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
on-ground/in-ground	on-ground
Soil quality	>20cm Béton C20/25

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:





PURGE ET SYNCHRONISATION DES VERINS

***Public price Exl. Tax : €15,999**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)