

Scissor lift 5.5T auxiliary lift 4.5T tech control in-ground

Reference : PE 6352T



Item name	Scissor lift 5.5T auxiliary lift 4.5T tech control in-ground
Bar code	3701555318134
Text	<p>Particularly suitable for technical inspections, geometries and repairs. Built-in for LV and LCV. Maximum safety: mechanical safety rack on main and auxiliary scissors for position stabilization. Auxiliary lift capacity 4.5T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for extra durability. Supplied with 2 pneumatically locked oscillating plates and 2 12-movement play plates. Supplied with 1 LCD screen console and a radio remote control to set the play plates in motion. Equipped with rails for optional lifting crossbar. PE 7100</p>
Product highlight	ideal undercarriage control
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- lifting height: 0-1950mm- track width/length: 690/5700mm- system synchronization: photo cell- control panel- drive power: 3kw- drive voltage: (3 phases + Neutral) 400V/50Hz- air supply required 6-8 bar.- pneumatic oscillating plates

- Epoxy paint
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Width 5,700 mm

Product weight (kg) 3,303 kg

Max. height 1,950 mm

Maximum load (T) 5.50 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6352T-1 - Scissor lift 5.5T auxiliary lift 4.5T tech control in-ground 1/4
 1 x PE 6352T-2 - Scissor lift 5.5T auxiliary lift 4.5T tech control in-ground 2/4
 1 x PE 6352T-3 - Scissor lift 5.5T auxiliary lift 4.5T tech control in-ground 3/4
 1 x PE 6352T-4 - Scissor lift 5.5T auxiliary lift 54.5T tech control in-ground 4/4
 4 x [SA 3012 - Hv46 hydraulic oil 5l](#)

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required YES

Circuit breaker/Cable section 16A D / 5x2.5mm²

on-ground/in-ground in-ground

Soil quality >20cm Béton C20/25



***Public price Exl. Tax : €20,999**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)