# 1/2" d. impact wrench set 1600Nm for wheels (19pcs)

Reference : OP 1650BL



| | |
|---|---|
| **Item name** | 1/2" d. impact wrench set 1600Nm for wheels (19pcs) |
| **Bar code** | 3701555322193 |
| **Introduction** | The OP 1650BL pack is the "ready-to-use" solution for workshops looking to equip themselves efficiently on a controlled budget. This package combines the striking power of the OP 1622BL impact wrench (1600Nm) with essential striking accessories, guaranteeing immediate start-up for all LV and LCV maintenance operations. |
| **Text** | Gross Power (1600Nm): Includes 1/2" impact wrench OP 1622BL capable of loosening the most stubborn assemblies.<br>Jumbo Hammer mechanism: Equipped with a unique oversized hammer for a direct and powerful strike, while simplifying internal tool maintenance.<br>Complete Accessory Kit: Comes with a selection of impact sockets and the necessary fittings, avoiding additional purchases and wasted time.<br>Robust Carrying Case: Organized storage and protection of workshop devices against shock and dust, making them easy to store and move.<br>B-Line profitability: A complete package offering the best compromise between work force and financial investment.<br><br>The OP 1650BL is the strategic choice for equipping a new employee or an additional workstation. It's the assurance of having a high-performance tool and its dedicated accessories at hand, with the guarantee of a competitive price. |
| **Product highlight** | One-hand reverser |
| **Specifications** | |

| | |
|---|---|
| | Specifications:<br>- loosening torque: 1600Nm<br>- max. tightening torque: 880Nm<br>- speed: 8,500 rpm<br>- connection: 1/4"<br>- recommended hose diameter: 3/8" - 10mm<br>- supply pressure: 6.3bar<br>- consumption: 184l/min<br>- length: 159mm<br>- net weight: 1.8kg<br>- supplied with fitting<br><br>Features :<br>- 4-position variator<br>- handle exhaust system<br>- one-hand reverser<br><br>EN ISO 11148-6:2012 |
| **Contents** | Contents:<br>- OP1622BL: 1/2" impact wrench<br>- 3 special impact wrench sockets for Aluminum rims: 17-19-21 mm<br>- 10 1/2" hex impact sockets: 9-10-11-13-14-17-19-22-24-27 mm<br>- 1/2" extension bar, 125 mm<br>- 4 mm Allen wrench<br>- oil<br>- oil gun<br>- comes with a coupling |
| **Warranty period** | 2 years |
| **Recesses** | Hex female |
| **Decibel level** | 94.90 dB |
| **Vibrations** | 4.96 m/s2 |
| **More** | Use oiler |
| **Length (mm)** | 159 mm |
| **Product weight (kg)** | 1.80 kg |
| **Tariff code** | Tariff Normal (TN) |
| **Drive** | 1/2" |
| **Product range** | B-Line |
| **Warranty Procedure** | DIAGNOSTIC |
| **Customer benefit** | Only 1.8Kg! |




***Public price Exl. Tax : €119**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)