

Pneumatic injector extractor

Reference : OP 9111



Item name Pneumatic injector extractor

Bar code 3701555323282

Introduction This pneumatic injector extractor has been specially designed to overcome the most seized injectors on common-rail diesel engines.

Thanks to its powerful pneumatic cylinder, it enables fast, effortless extraction, while limiting the risk of breakage or damage to surrounding components.

Text Highlights:

- Vertical pneumatic action: automatic hammering from top to bottom at high speed to effectively disengage jammed injectors.
- No Engine removal required: supplied with an extension and three forks (12 mm, 13.5 mm, 16 mm) enabling the injector head to be picked up from below, without prior disassembly.
- Regulated working pressure: 5 to 8 bar (< 100 L/min).
- Universal compatibility: suitable for Bosch, CAT, Cummins, Denso injectors, and many others.

Product highlight Supplied in a foam box for optimal storage and protection

Specifications Specifications :

- max. cylinder height: 150mm
- min. cylinder height: 135mm
- overall flexible length: 780mm

Contents

Package contents :

- 1 high-performance pneumatic cylinder
- 1 mounting extension
- 3 holding forks (12 / 13.5 / 16 mm)
- 19 pieces (screws and adapters) M8/M10/M12/M14/M15/M17/M19
- 1 pneumatic supply hose with quick-release coupling

Advice

Designed primarily for injector extraction on common-rail diesel engines.
May also fit certain gasoline injectors, depending on adapter compatibility.

Warranty period

2 years

Tariff code

Tariff Normal (TN)

2
WARRANTY



TN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)