Hgv jack 22T

Reference : OH 5000



Item name	Hgv jack 22T
Bar code	3701555323909
Specifications	Specifications: - Allows for quick and effortless operation - Overload protection system - 1 stage: 22T - Equipped with a descent speed control valve for added safety - Long T-handle for easy positioning of the jack under the vehicle - 3-position handle: 90°, 45°, 0° with metal locking system - Min. height: without extension, 225 mm - Max. height: without extension, 428 mm - Max. height: with extension, 528 mm - Height without handle: 175 mm - Total height with handle: 1,400 mm - Length: 820 mm with the handle at 0°, 1,430 mm in the intermediate 45° position, and 1,800 mm in the 90° position - Chassis and wheel length: 580 mm - Width: 278 mm - Extensions: 10–65–100 mm - Supply pressure: 7.5–8.5 bar - Weight: 33 kg
Applications	Applications: Truck, trailer, bus, farm machinery, public works.

Warranty period	2 years
Length (mm)	820 mm
Width	278 mm
Product weight (kg)	33 kg
Max. height	428 mm
Min. height	225 mm
Jack type	Hydropneumatic
Maximum load (T)	22 T
Tariff code	Tariff Normal (TN)
Warranty Procedure	EASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)