



2-column asymmetrical low-deck post lift 4T 240V

Reference : PE 2240M



Item name	2-column asymmetrical low-deck post lift 4T 240V
Bar code	3701555326634
Text	<p>Post lift designed to facilitate installation and alignment of pre-assembled columns. Option: PE 2241 2 reinforcements to solve the problem of screeds which do not meet the minimum thickness requirement of 200mm (can cover up to 150mm) or which present a slight flatness problem. Electro-hydraulic elevator. Pusher cylinder on cable, carriage pulled by chain. Telescopic arms in asymmetrical version with 2-stage arms: 820-1320mm and 3-stage arms from 690 mm-1290 mm.</p>
Product highlight	Pre-assembled columns
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- lifting height: 95-1900mm- drive power: 2.2kW- drive voltage: (1~ + N) 240V/50/Hz- adjustable buffers on 2-stage screw travel 85-170mm- automatic release of safety catches- emergency lowering system in case of power failure- steel engine- system synchronization: by cable- intermediate stop 20cm above ground for user safety and anti-crushing audible signal- engine protection cover

- door protection on columns
- protective strip for cylinder, chain and cables included on each column
- Epoxy paint

Advice Please consult us for installation and commissioning.
Under warranty, installation and commissioning must be carried out by a professional.
Transport costs not included.

Warranty period 2 years

Power 2200W

Voltage 240V

Width 3,385 mm

Height 2,856 mm

Max. height 1,900 mm

Min. height 95 mm

Maximum load (T) 4 T

Tariff code Tariff Equipment (TE)

Warranty Procedure INTERVENTION

Customer benefit Supplied with ground fixing kit and HV46 hydraulic oil

Pneumatic power supply required NO

Circuit breaker/Cable section 10A D / 5x2.5mm²

Soil quality >20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)