



Double scissors post lift 3.5T 240V to be installed or flush-mounted

Reference : PE 6400M



Item name	Double scissors post lift 3.5T 240V to be installed or flush-mounted
Bar code	3701555326641
Text	Particularly suited to paint, body repair and quick service activities. Choice of installation: free-standing or built-in. Easy access: low 105mm ground clearance, lockable ramps to extend platforms. Maximum comfort and safety: double hydraulic master-slave safety system.
Product highlight	Can be used free-standing or built-in
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 105-1990mm- track width/length: 650/1547-2077mm- system synchronization: photo cell- control panel- drive power: 2.2kw- Aluminum engine- drive voltage: (1 ~ + N) 240V/50/Hz- emergency lowering system in case of power failure- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal-supplied with 4 x 35 mm buffers
Advice	Please consult us for installation and commissioning. Under warranty, installation and commissioning must be carried out by a professional.

Transport costs not included.

Warranty period	2 years
Power	2200W
Voltage	240V
Length (mm)	2,077 mm
Width	1,990 mm
Height	1,900 mm
Maximum load (T)	3.50 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6400M-1 - Double scissors post lift 3.5T 240V to be installed or recessed 1/2 1 x PE 6400M-2 - Double scissors post lift 3.5T 240V to be instal. or flush-mounted 2/2 3 x SA 3012 - Hv46 hydraulic oil 5l

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required YES

Circuit breaker/Cable section 16A D / 3x2.5mm²



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)