

## Double scissors post lift 3.5T 240V to be installed or flush-mounted

Reference : PE 6400M



|                          |   |
|--------------------------|---|
| <b>Item name</b>         | Double scissors post lift 3.5T 240V to be installed or flush-mounted  |
| <b>Bar code</b>          | 3701555326641   |
| <b>Text</b>              | Particularly suited to paint, body repair and quick service activities.<br>Choice of installation: free-standing or built-in.<br>Easy access: low 105mm ground clearance, lockable ramps to extend platforms.<br>Maximum comfort and safety: double hydraulic master-slave safety system.   |
| <b>Product highlight</b> | Can be used free-standing or built-in   |
| <b>Specifications</b>    | Specifications : <ul style="list-style-type: none"><li>- lifting height: 105-1990mm</li><li>- track width/length: 650/1547-2077mm</li><li>- system synchronization: photo cell</li><li>- control panel</li><li>- drive power: 2.2kw</li><li>- Aluminum engine</li><li>- drive voltage: (1 ~ + N) 240V/50/Hz</li><li>- emergency lowering system in case of power failure</li><li>- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal</li><li>-supplied with 4 x 35 mm buffers</li></ul> |
| <b>Advice</b>            | Please consult us for installation and commissioning.<br>Under warranty, installation and commissioning must be carried out by a professional.<br>Transport costs not included.   |

|                                    |  |
|------------------------------------|--|
| <b>Warranty period</b>             | 2 years  |
| <b>Power</b>                       | 2200W  |
| <b>Voltage</b>                     | 240V   |
| <b>Length (mm)</b>                 | 2,077 mm   |
| <b>Width</b>                       | 1,990 mm   |
| <b>Height</b>                      | 1,900 mm   |
| <b>Maximum load (T)</b>            | 3.50 T   |
| <b>Tariff code</b>                 | Tariff Equipment (TE)  |
| <b>Composition of nomenclature</b> | 1 x PE 6400M-1 - Double scissors post lift 3.5T 240V to be installed or recessed 1/2<br>1 x PE 6400M-2 - Double scissors post lift 3.5T 240V to be instal. or flush-mounted 2/2<br>3 x <a href="#">SA 3012 - Hv46 hydraulic oil 5l</a> |

#### Warranty Procedure INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Pneumatic power supply required** YES

**Circuit breaker/Cable section** 16A D / 3x2.5mm<sup>2</sup>



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)