

Tire changers with or without pneumatic finger + wheel lifter

Reference : DM 3002



Item name Tire changers with or without pneumatic finger + wheel lifter

Bar code 3701555330662

Introduction Automatic tire changer with a chuck plate and arm that can be used either in leverless mode or with a tire-changing lever.
2-speed inverter motor for greater speed, safety, and reliability.
The special support arm, used to apply pressure to the bead, automatically returns to its resting position at the end of the job, so the operator does not have to change position during operations.
Ultra-fast wheel clamping system using cones and a clamping collar.
Two bead-separating discs offset from the rim's center hole for better and faster penetration and immediate tire detachment.
The two bead-separating discs enable simple, fast, and risk-free bead separation. It is also perfect for coupling operations and positioning the bead in its seat. Ideal for all types of tires, from soft to run-flat.
It is possible to disengage the bead-separator disc and activate its tilting motion to change the bead-separation angle and increase penetration into the rim. Very effective for soft tires.
The new bead breaker assembly was designed using a new construction concept capable of eliminating flex and play through a combination of levers that eliminate the need for adjustments while simultaneously increasing reliability.
The three bead-separating positions allow for work on wheels ranging from 12 to 34 inches (12-30, 14-32, and 16-34).
The upper disc is held in the rest position by an automatic actuating lever, allowing the

operator to work comfortably.

Pneumatically operated double arm.

Specially designed for the effortless mounting and demounting of all LV, light commercial vehicle, and 4x4 tires.

A fully equipped and easy-to-use machine.

This assistant, compatible only with our DM 3000 tire changer, will allow you to work quickly and effortlessly.

Comes with a wheel lifter featuring a foot-operated pneumatic control. You can lift the wheel to position it on the tire changer's mandrel. This allows you to place the wheel on the table quickly with minimal physical effort, thereby reducing the risk of musculoskeletal disorders (MSDs).

Text

For installation and setup, please contact us.

Under the terms of the warranty, installation and setup must be performed by a professional.

Product highlight

Can be used with or without the pneumatic finger

Specifications

Specifications:

Tire changers

- Air pump with pressure gauge
- Inlet air pressure regulator set to 10 bar.
- Maximum wheel weight: 80 kg
- Chuck with rim clamping for 12- to 34-inch rims.
- Maximum outer tire diameter: 47 inches, 1200 mm
- Maximum tire width: 16 inches
- Max. chuck rotation torque: 1200 Nm
- 2 speeds without a switch:
 - Rotation speed 1: 7 rpm
 - Rotation speed 2: 16 rpm
- Ergonomic and intuitive foot pedal that can be easily removed from the front
- Operating pressure: 8–10 bar
- Inflation pressure limiter: 3.5 bar
- Air filter and oil lubricator
- Noise level < 70 dB
- Power: 0.75 kW, 2 speeds
- Bead breaker cylinder force at 10 bar: 1,227 kg
- Maximum bead breaker disc opening: 670 mm, 26 inches
- Heel press cylinder force at 10 bar: 430 kg
- Dimensions: 1980 x 1880 x 2300 mm
- Power supply: 240 V, 1-phase, 50–60 Hz
- Net weight: 395 kg

Wheel Lift

Specifications:

- Max. load: 80 kg
- Max. lifting height: 620 mm
- Lifting platform dimensions: 320 x 275 mm

Contents

Includes:

- heel-removal lever
- plastic lever
- set of plastic inserts for the mounting tool
- plastic guards for the centering cone
- rubber guards for the chuck and drive shaft
- 70mm diameter plastic cone
- reduction ring for the chuck
- WDK heel clamp
- set of rubber guards
- knob wrench for quick-release clamping
- cleaning brush
- lubricator + filter + pressure regulator
- replacement O-rings for clamping system.

Warranty period 2 years

Power 1200W

Decibel level 68 dB

Voltage 240V

Length (mm) 1,880 mm

Width 1,980 mm

Height 2,300 mm

Product weight (kg) 395 kg

Tariff code Tariff Equipment (TE)

Warranty Procedure DIAGNOSTIC

Customer benefit Option to choose between a leverless arm or a traditional mounting

Pneumatic power supply required YES



***Public price Exl. Tax : €16,980**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)