

Carrossier 3.6T 160cm Extra-Low Scissor Lift (free-standing/built-in)

Reference : PE 6236T160



Item name	Carrossier 3.6T 160cm Extra-Low Scissor Lift (free-standing/built-in)
Bar code	3701555330747
Text	Particularly well-suited for painting, body repair, and quick-service operations. Installation options: free-standing or built-in. Easy access: low ground clearance of 110 mm, lockable access ramps to extend the platforms. Maximum comfort and safety: controlled by a dual master-slave hydraulic safety system combined with a rack-and-pinion mechanism for sustained position locking. Auto body lift with 160 cm locking height, CARSAT-eligible
Product highlight	Can be used as a free-standing unit or built-in
Specifications	Specifications: - Lifting height: 110–1,600 mm - Width/length of bearing paths: 630/1,480–2,090 mm - Synchronization system: photocell - Required air pressure: 6–8 bar. - control panel - drive power: 3 kW - drive voltage: (3-phase + neutral) 400 V/50 Hz - Emergency descent system in case of power failure - Intermediate stop 20 cm above the floor for user safety and an anti-crushing audible alarm - Comes with 4 bumpers

Advice	For installation and setup, please contact us. Under the warranty, installation and setup must be performed by a professional. Shipping costs not included.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	2,090 mm
Width	2,110 mm
Height	960 mm
Product weight (kg)	904 kg
Max. height	1,600 mm
Min. height	110 mm
Maximum load (T)	3.60 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6236T-1 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 1/3 1 x PE 6236T-2 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 2/3 1 x PE 6236T-3 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 3/3 3 x SA 3012 - Hv46 hydraulic oil 5l

Warranty Procedure INTERVENTION

Customer benefit	Comes with HV46 hydraulic oil and a floor mounting kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm ² (3PH + N + T)
Soil quality	>20cm Béton C20/25

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:

2
WARRANTY

400V



[PURGE ET SYNCHRONISATION DES VERINS](#)



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)