

Automatic wheel balancers 3d digital display + laser pointer

Reference : EQ 2100



Item name Automatic wheel balancers 3d digital display + laser pointer

Bar code 3700461482137

Introduction Motorized wheel balancer with large digital display. Automatic 3-parameter measurement for quick, easy and precise balancing of LV, LCV and 4x4 wheels. Balancing can be performed in dynamic or static mode, with unbalance optimization and the hidden weight program available. A large number of programs will enable you to work on any type of rim, according to the user's needs and habits. It will also be possible to work with 2 operators at the same time for greater speed, and the long length of its shaft will enable it to cover even rims with very large offsets. For added comfort, the balancer is equipped with an electromagnetic brake that stops the wheel at the precise point to be balanced in ALS programs. A precision laser and light are automatically activated for ultra-precise bonding, with no risk of residual or wasted lead.

Text Features :

- European software
- automatic cycle
- multifunction keys
- static and dynamic program (2 planes) in a single run
- 9 programs: 7 Alu (hidden mass) +Optimization+Static Moto
- self-calibration: 50g mass
- self-diagnosis: fault code
- multiple operator function
- simultaneous display of weights and weight positions
- automatic stop on weight position with led lighting inside rim

- electromagnetic brake, lockable at will
- measurement accuracy: ± 1 g
- display accuracy: 1g/5g

Product highlight Laser pointer
Electro-magnetic brake
Automatic rigging

Specifications Specifications :

- power supply: 240V-50Hz
- power: 90W
- dimensions open housing: 1550x1160x1490mm
- noise level < 69dB
- digital display (5min standby)
- maximum wheel diameter: 1100mm
- max. wheel weight: 70kg
- max rim diameter: 28 inches
- rim width: from 1.5 to 20 inches
- automatic measurement of 3 parameters: offset-diameter-width
- laser pointer for weight positioning
- safety housing with automatic start
- measurement cycle time: 7s
- rotation speed: 140rpm
- shaft: L.210mm-Ø40mmx4mm
- compartmentalized tray for cones and masses
- 4 storage supports
- weight positioning clamp
- weight: 149kg

Contents Supplied with :

- EQ6521BL: 4 cones from 42 to 137mm Ø40mm
- 12mm hexagonal wrench
- SA8305: rim width compass
- SA8905: 50g calibration weight
- OC8034: multifunction weight clamp
- EQ6404BL: Ø40x4mm quick nut with bowl/joint/compression ring

Options Installation et mise en service, nous consulter.
Dans le cadre de la garantie, installation et mise en service doivent être effectuées par un professionnel.

Advice Electromagnetic brake

Warranty period 2 years

Power 90W

Voltage 240V

More Products with electrical plug

Product weight (kg) 149 kg

Tariff code Tariff Equipment (TE)

Warranty Procedure INTERVENTION

Quick tip videos

Click on the operation you are interested in to watch the **video**:



[POWER SUPPLY BOARD REPLACEMENT](#)



[CPU REPLACEMENT](#)



[MEASUREMENT ARM CALIBRATION](#)



[PICK-UP SENSOR REPLACEMENT](#)

Operation videos

Click on the operation you are interested in to watch the video:

2
WARRANTY



90
W



TE

[COMMISSIONING](#)
[CALIBRATION](#)
[SHEET METAL RIM BALANCING](#)
[ALUMINUM RIM BALANCING](#)

***Public price Exl. Tax : €2,599**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)