Electric brake bleeder and clutch 5-20l 3.5bar

Reference : HU 1102




Item name	Electric brake bleeder and clutch 5-20l 3.5bar
Bar code	3700461486852
Introduction	Automatic shut-off when the level in the canister is too low. Fitted with a bleed and priming connector when changing the fluid. Checks tightness of low-pressure brake circuit. Suction function for expansion tank, with graduated used fluid recovery canister (1.5L).
Product highlight	Continuous-pressure liquid thrust, pulsating flow
Specifications	Specifications: - 240V power supply (5-meter cord) - Equipped with an ON/OFF switch - Features a 0–3.5 bar pressure regulator that maintains fluid pressure during pulsed flow - pressure gauge - suitable for clutches and brakes (compatible with ABS, EDS, ESP, and SBC systems) - capacity: 5 to 20 liters, allowing for multiple operations - catch pan dimensions: - height: 500 mm - width: 300 mm - Depth: 480 mm - Interchangeable reservoir: ensures compatibility with DOT 3, DOT 4, DOT 5, and DOT 6 fluids - Hose length: 3.5 m - Dimensions: 850 x 400 x 330 mm

	- Weight: 23 kg
Contents	Comes with a metal cap, Ø 46 mm x 3.5
Warranty period	3 years
Voltage	240V
More	Products with electrical plug
Cable length	5 m
Length (mm)	850 mm
Width	400 mm
Height	300 mm
Product weight (kg)	23 kg
Capacity (ml)	20,000 ml
Capacity (l)	20 l
Tariff code	Tariff Normal (TN)
Warranty Procedure	DIAGNOSTIC

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:





REMPLACEMENT DU CAPTEUR DU PURGEUR DE FREIN



PURGE DU CIRCUIT DE PURGEUR DE FREIN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)