

Electric brake bleeder and clutch 5-20l 3.5bar

Reference : HU 1102



Item name	Electric brake bleeder and clutch 5-20l 3.5bar
Bar code	3700461486852
Introduction	Automatic shut-off when the level in the canister is too low. Fitted with a bleed and priming connector when changing the fluid. Checks tightness of low-pressure brake circuit. Suction function for expansion tank, with graduated used fluid recovery canister (1.5L).
Product highlight	Continuous-pressure liquid thrust, pulsating flow
Specifications	Specifications : <ul style="list-style-type: none">- 240V power supply (5m cord)- equipped with On/Off switch- fitted with a 0-3.5bar pressure regulator with pulsating liquid thrust control- pressure control gauge- suitable for clutches and brakes (compatible with ABS, EDS, ESP, SBC systems)- 5 to 20-liter capacity, allowing multiple operations- dimensions of drip tray :<ul style="list-style-type: none">- height: 500mm- width: 300mm- depth: 480mm- interchangeable canister: ensures DOT3/DOT4/DOT5/DOT6 liquid compatibility- flexible hose L.3.5m- dimensions: 850x400x330mm- weight: 23kg

Contents	Supplied with metal cap Ø46mmx3.5
Warranty period	3 years
Voltage	240V
More	Products with electrical plug
Cable length	5 m
Length (mm)	850 mm
Width	400 mm
Height	300 mm
Product weight (kg)	23 kg
Capacity (ml)	20,000 ml
Capacity (l)	20 l
Tariff code	Tariff Normal (TN)

Warranty Procedure DIAGNOSTIC

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:



[REPLACEMENT DU CAPTEUR DU PURGEUR DE FREIN](#)



TN



[PURGE DU CIRCUIT DE PURGEUR DE FREIN](#)

TENSION240V.jpg

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)