

## Reel 1x6mm<sup>2</sup> for earthing

Reference : OE 0501



<b>Item name</b>	Reel 1x6mm <sup>2</sup> for earthing
<b>Bar code</b>	3700461419256
<b>Product highlight</b>	ATEX 94/9/CE explosion-proof clamp
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- the winder is not explosion-proof</li><li>- IP42</li><li>- rated current: 20A</li><li>- insulation voltage: 2.5kV</li><li>- single-core cable 1x6mm<sup>2</sup> H05V-F color yellow/green</li><li>- stop device every 50cm</li></ul> <p>Clamp specifications :</p> <ul style="list-style-type: none"><li>- clamp version II2GD Ex d IIC T6-Ex tD A21/IP65/Temp 85°C</li><li>- compliant with standards: EN 60079-0, EN 60079-1, EN 61241-0, EN 61241-1</li><li>- CESI 03 ATEX 94/9/CE approval</li><li>- use: explosive atmosphere environment in presence of group IIC gas and flammable powders</li><li>- with anti-tear opening system</li><li>- reliable, robust, handy and easy to use</li><li>- insulation voltage: 3kV</li><li>- rated current: 10A</li><li>- opening range: 3 to 20mm</li><li>- dimensions: 250x110x35mm</li></ul>

**Warranty period** 2 years  
**Power** 1800W  
**Cable length** 14 m  
**Product weight (kg)** 6.50 kg  
**Tariff code** Tariff Normal (TN)

**Warranty Procedure**DIAGNOSTIC



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)