

## Voltage safety tester

Reference : OE 3010



<b>Item name</b>	Voltage safety tester
<b>Bar code</b>	3700461456565
<b>Introduction</b>	Indispensable for the building industry or electric vehicles, the VAT tester is used to check that no voltage is present on a circuit before starting work, in compliance with NF C18-510 and IEC 61243-3VAT/DDT standards.
<b>Text</b>	Compatible with : B1L, B1VL, B1TL, B2L, B2VL, B2TL, BCL, BEL, BRL, B1XL, B2XL.
<b>Product highlight</b>	Complies with NF C18-510 and IEC 61243-3VAT/DDT standards
<b>Specifications</b>	Specifications : <ul style="list-style-type: none"><li>- continuity test</li><li>- 30mA differential circuit-breaker test</li><li>- waterproof and dustproof</li><li>- voltage test: 2 to 690V AC/DC 750V DC with audible range change emission</li><li>- auto AC/DC</li><li>- resistance measurement up to 2kOhm</li><li>- audible continuity test <math>R &lt; 2k\Omega</math></li><li>- operating frequency DC 50-60Hz and 400Hz</li><li>- self-test of probe tips, cord, display and 9V battery</li><li>- low impedance: 390kOhm</li><li>- 19mm probe center distance (for circuit breakers)</li></ul>
<b>Warranty period</b>	2 years

**IP** IP65  
**More** Powered by battery  
**Cable length** 0.90 m  
**Length (mm)** 172 mm  
**Width** 64 mm  
**Height** 38 mm  
**Product weight (kg)** 0.33 kg  
**Tariff code** Tariff Normal (TN)

**Warranty Procedure** DIAGNOSTIC



**IP 65  
PRO**



**TN**

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)