

Voltage safety tester

Reference : OE 3010



Item name	Voltage safety tester
Bar code	3700461456565
Introduction	Indispensable for the building industry or electric vehicles, the VAT tester is used to check that no voltage is present on a circuit before starting work, in compliance with NF C18-510 and IEC 61243-3VAT/DDT standards.
Text	Compatible with : B1L, B1VL, B1TL, B2L, B2VL, B2TL, BCL, BEL, BRL, B1XL, B2XL.
Product highlight	Complies with NF C18-510 and IEC 61243-3VAT/DDT standards
Specifications	Specifications : <ul style="list-style-type: none">- continuity test- 30mA differential circuit-breaker test- waterproof and dustproof- voltage test: 2 to 690V AC/DC 750V DC with audible range change emission- auto AC/DC- resistance measurement up to 2kOhm- audible continuity test $R < 2k\Omega$- operating frequency DC 50-60Hz and 400Hz- self-test of probe tips, cord, display and 9V battery- low impedance: 390kOhm- 19mm probe center distance (for circuit breakers)
Warranty period	2 years

IP	IP65
More	Powered by battery
Cable length	0.90 m
Length (mm)	172 mm
Width	64 mm
Height	38 mm
Product weight (kg)	0.33 kg
Tariff code	Tariff Normal (TN)

Warranty ProcedureDIAGNOSTIC



***Public price Exl. Tax : €119**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)