

MEGOHMMETER 1000V CAT. III & 600V CAT. IV

Reference : OE 4002



Item name	MEGOHMMETER 1000V CAT. III & 600V CAT. IV
EAN code	3700461471568
Intro	<p>Specially designed for hybrid and electric vehicles, this device can measure the isolation of electrical equipment, as well as a voltage up to 1000V.</p> <p>It allows the measurement of DC and AC voltage, DC and AC current, temperature, resistance, capacity, isolation and frequency.</p>
Text	<p>Suitable for the "low voltage" requirements of authorisations: BCL, B2VL, B2TL, B2XL</p> <p>...</p>
Product highlight	Suitable for hybrid and electric vehicles
Specifications	<p>Specifications:</p> <p>Complies with IEC/EN 61010-1 1000V CAT III, 600V CAT IV.</p> <p>1000V DC Voltage, 750V AC Voltage (TRMS).</p> <ul style="list-style-type: none"> - DC voltage: 600mV-6V-60V-600V-1000V - AC voltage 600mV-6V-60V-600V-750V - DC current: 60mA-400mA - AC current: 60mA-400mA - 6600 counts (except for capacity, temperature and insulation measurement) - when the input terminals are V and COM, the protective voltage overload is up to 250V AC (TRMS). - when the input terminals are mA and COM, the protection current is 0.4A. - when the input terminals are Hi and Lo, the protective voltage overload is 600V. - display of minimum average values

- 4 AA batteries (NEDA 15A or IEC LR6) for 1000 hours of battery life for the insulation test.
 - the multimeter can perform at least 1000 insulation tests with new alkaline batteries at room temperature.
- These are standard tests of 1000V in 1M Ω with a duty cycle of 5 seconds on and 25 seconds off.
- resistance: 600ohm-6kohm-60kohm-600kohm-6Mohm-60Mohm
 - insulation measurement range: 0.01M Ω to 2G Ω .
 - isolation test voltages: 50V, 100V, 250V, 500V, 1000V.
 - insulation original voltage: +20%, -0%.
 - insulation short circuit test current: 1.5mA nominal.
 - automatic discharge of insulation: Discharge time <1 second for C = 1 μ F or lower.
 - detection of the live isolation circuit: block the test if the voltage at the terminal is >20V before starting the test.
 - insulation resistance: 50V (5-50Mohm) - 100V (0-100Mohm) - 250V (0-250Mohm) - 500V (0-500Mohm) - 1000V (0-2Gohm)
 - calculation of dielectric absorption ratio (DAR) and automatic polarization index (PI);
 - maximum capacitive load of insulation: operates up to a load of 1 μ F.
 - storage temperature: -40°C to 60°C.
 - operating temperature: 0°C to 40°C.
 - storage altitude: 12000m
 - operating altitude: 2000m 1000V CAT III, 3000m 1000V CAT II
 - temperature: -30 to 1300°C
 - temperature coefficient: 0.05 (specified accuracy) per °C for temperatures <18°C or >28°C.
 - relative humidity: 40%~75%.
 - dimensions: 205(L) 102(W) 58(H)mm.
 - weight: about 390g.
 - electrical safety categories: CAT III 1000V, this device can be used in a category 3 medium (shown in the table on the left) at a maximum voltage of 1000V, and in a category 4 medium at a maximum voltage of 600V.

Contents

Contents:

- 1x Megohmmeter
- 1x pair of measuring cables
- 1x pair of crocodile clips
- 1x MS 3204
- 1x temperature probe (Thermocouple type K)
- 1x transport house
- 1x transport strap (shoulder strap)
- 4x LR6 batteries

Warranty period 2 years

Tension 1000V

More Powered by battery

Cable length 1.20 m

Length 205.00 mm

Width 102.00 mm

Height 58.00 mm

Tariff code Tariff Normal (TN)

Warranty ProcedureDIAGNOSTIC



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)