

WHEEL BEARING PULLER ON SITE PEUGEOT/CITROEN/RENAULT

Reference : OM 3430



Item name	WHEEL BEARING PULLER ON SITE PEUGEOT/CITROEN/RENAULT
Bar code	3700461457357
Introduction	<p>Enables fast, safe removal and fitting of wheel bearings directly on vehicles.</p> <p>Specially designed cloches for perfect support on the pivots, adapted pressure rings for extraction and correct positioning of the bearings.</p> <p>Removal of the shock absorber strut, suspension arm and camber adjustment on certain vehicles is no longer necessary (time saving of around 1 hour).</p> <p>The extraction bells feature notches to avoid disassembly of the ABS sensors.</p>
Product highlight	Time-saving: no need to disassemble ABS sensor
Contents	<p>Contents:</p> <ul style="list-style-type: none">- 2 bell rings- 1 bell: outside Ø 104mm, inside Ø 84mm-90mm, height 85mm- 1 conical adapter ring: outside Ø 99mm, inside Ø 74mm, height: 44mm- 1 conical adapter ring with ABS notch: outside-Ø 99mm, inside-Ø 74mm, height 44mm- 1 cylindrical adapter ring with ABS notch: outside-Ø 100mm, inside-Ø 84mm, height: 53mm- 1 cylindrical adapter ring with ABS notch: outside-Ø 94mm, inside-Ø 88mm, height: 44mm- centering rings: 35-37-42-45-60-75mm- pressure rings: 65-72-82-83mm- M20 extraction screw and nut- weight: 11.70kg

Applications	Traditional bearings from Ø65mm to Ø90mm
Options	Hydraulic extractor OM9384 is suggested for highly seized bearings.
Warranty period	2 years
Product weight (kg)	11.70 kg
Tariff code	Tariff Normal (TN)
Warranty Procedure	EASY



CLAS EQUIPEMENTS
 83, chemin de la CROUZA
 73800 CHIGNIN
 France

Tel : +33 (0) 4 79 72 62 22
 Fax :

Monday to Friday - From 8 to 12h
 and from 13h30 to 17h30 (16h30 on
 Friday)