Wheel bearing puller on site Peugeot/Citroen/Renault

Reference : OM 3430



Item name	Wheel bearing puller on site Peugeot/Citroen/Renault
Bar code	3700461457357
Introduction	Enables fast, safe removal and fitting of wheel bearings directly on vehicles. Specially designed cloches for perfect support on the pivots, adapted pressure rings for extraction and correct positioning of the bearings. Removal of the shock absorber strut, suspension arm and camber adjustment on certain vehicles is no longer necessary (time saving of around 1 hour). The extraction bells feature notches to avoid disassembly of the ABS sensors.
Product highlight	Time-saving: no need to disassemble ABS sensor
Contents	Contents: - 2 bell rings - 1 bell: outer diameter 104 mm, inner diameter 84 mm–90 mm, height 85 mm - 1 conical adapter ring: outer diameter 99 mm, inner diameter 74 mm, height: 44 mm - 1 conical adapter ring with ABS notch: outer diameter 99 mm, inner diameter 74 mm, height 44 mm - 1 cylindrical adapter ring with ABS notch: outer diameter 100 mm, inner diameter 84 mm, height: 53 mm - 1 cylindrical adapter ring with ABS notch: outer diameter 94 mm, inner diameter 88 mm, height: 44 mm - centering rings: 35-37-42-45-60-75 mm - pressure rings: 65, 72, 82, 83 mm - pull-out bolt and nut M20

	- weight: 11.70 kg
Applications	Traditional bearings from Ø65mm to Ø90mm
Options	Hydraulic extractor OM9384 is suggested for highly seized bearings.
Warranty period	2 years
Product weight (kg)	11.70 kg
Tariff code	Tariff Normal (TN)
Warranty Procedure	EASY



***Public price Exl. Tax : €499**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)