

## Ribbed pulley puller with interchangeable arms

Reference : OM 4067



<b>Item name</b>	Ribbed pulley puller with interchangeable arms
<b>Bar code</b>	3700461486227
<b>Introduction</b>	This tool removes pulleys from multi-groove crankshafts without damaging them. The claws are adjusted by translation using the worm screw for better centering of the tool on the pulley. Reduced footprint for engine-installed operation.
<b>Product highlight</b>	Interchangeable ball-locking claws
<b>Specifications</b>	Specifications : <ul style="list-style-type: none"><li>- adjustable claws from Ø30 to 185mm</li><li>- claw offset: 15mm</li><li>- thrust screw length: 90mm</li><li>- claw and thrust screw adjustment drive: 3/8" or 6 hex 17mm</li><li>- throat pitch: 3.56mm</li></ul>
<b>Options</b>	Option: <ul style="list-style-type: none"><li>- SA4067: 32mm offset arms kit + L.180mm push screw</li></ul>
<b>Warranty period</b>	2 years
<b>Tariff code</b>	Tariff Normal (TN)
<b>Product range</b>	Approved by SNR
<b>Warranty Procedure</b>	EASY

2  
WARRANTY



TN

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)