

Hydraulic extraction set

Reference : OM 9385



Item name Hydraulic extraction set

Bar code 3700461442742

Introduction

1. CONTENTS
2. SELECTION OF EXTRACTION SLEEVES
3. EXTRACTION
4. INSERTING THE NEW SILENT-BLOC

Text

Fig.1

- select the right bushes for the diameter and the extraction screw
- couple bushes and screw to hydraulic extractor
- secure assembly with adjusting nuts

Fig. 2

- operate the hydraulic control to extract the silent-bloc in the long bush

Fig. 3

- reverse assembly of bushes, place new silent-bloc and secure with adjusting nuts

Fig. 4

- actuate the hydraulic control: the silent-bloc will be inserted into its hole

Contents

Contents :

- SA9384: 18T hydraulic cylinder with 3/8" connection
- SA9385: threaded rod M10x1.5
- SA9386: threaded rod M12x1.75
- SA9387: threaded rod M14x1.5
- SA9388: threaded rod M16x2.0

- set of 22 short sockets 40mm
- set of 22 long sockets 110mm
- plastic case
- SA4215: 1/4"-3/8" interface fitting

Warranty period 2 years

Maximum load (T) 18 T

Tariff code Tariff Normal (TN)

Warranty ProcedureEASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)