Hydraulic extraction set

Reference : OM 9385



Item name	Hydraulic extraction set
Bar code	3700461442742
Introduction	1. CONTENTS 2. SELECTION OF EXTRACTION SLEEVES 3. EXTRACTION 4. INSERTING THE NEW SILENT-BLOC
Text	Fig.1 - select the right bushes for the diameter and the extraction screw - couple bushes and screw to hydraulic extractor - secure assembly with adjusting nuts Fig. 2 - operate the hydraulic control to extract the silent-bloc in the long bush Fig. 3 - reverse assembly of bushes, place new silent-bloc and secure with adjusting nuts Fig. 4 - actuate the hydraulic control: the silent-bloc will be inserted into its hole
Contents	Contents: - SA9384: 18T hydraulic cylinder with 3/8" connection - SA9385: M10x1.5 threaded rod - SA9386: M12x1.75 threaded rod - SA9387: M14x1.5 threaded rod - SA9388: M16x2.0 threaded rod

- set of 22 short sockets, 40 mm
- set of 22 long sockets, 110 mm
- plastic case
- SA4215: 1/4"-3/8" adapter

Warranty period 2 years

Maximum load (T) 18 T

Tariff code Tariff Normal (TN)

Warranty Procedure EASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)