

## Reinforced pneumatic spring compressor (2.4T) with articulated jaws

Reference : OP 3221



<b>Item name</b>	Reinforced pneumatic spring compressor (2.4T) with articulated jaws
<b>Bar code</b>	3700461479489
<b>Introduction</b>	Specially designed to fit and securely hold springs with widely spaced coils. Thanks to the innovative articulation system, adjustment is automatic when the spring is compressed.
<b>Product highlight</b>	Compliance 2006/42CE
<b>Specifications</b>	Specifications : <ul style="list-style-type: none"><li>- height: 1600mm</li><li>- ground connection :</li></ul> Length: 847mm width: 628mm <ul style="list-style-type: none"><li>- operating pressure: 6bar/maxi 10bar</li><li>- compression force 2452kg</li><li>- operating and maintenance instructions</li><li>- lower cup adjustable to 2 positions (e.g.: Chrysler long-travel shock absorber, Dodge RAM...)</li><li>- weight: 70kg</li></ul>
<b>Contents</b>	Contents : <ul style="list-style-type: none"><li>- OP2003: upper side jaw</li><li>- SA6915: lower cup 125-205mm</li><li>- SA6918: 1 cup Ø78 to Ø130mm</li><li>- SA6906: fall arrest support</li></ul>

**Warranty period** 5 years

**Product weight (kg)** 70 kg

**Maximum load (T)** 2.40 T

**Tariff code** Tariff Normal (TN)

**Product range** Approved by SNR

**Warranty Procedure** DIAGNOSTIC



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)