Special synthetic oil for screw compressors (5l)

Reference : OP 6813



Item name	Special synthetic oil for screw compressors (5l)
Bar code	3700461477669
Introduction	Oil specially designed for screw compressor lubrication.
Text	PAO (polyalphaolefin) synthetic technology. Formulated using only new raw materials and lubricating bases. Good thermal stability (discharge temperature >90°C). Immediate lubrication of screws even at high pressure (>10 bar). Enhanced anti-wear and anti-friction properties. Neutrality towards seals and elastomers. Excellent shear stability (lubricant film maintained). Maintains performance at all speeds (high viscosity index). Protects components and alloys (anti-corrosion and anti-oxidant additives). Extends equipment life and reduces maintenance costs. Miscible with other hydraulic fluids of the same type.
Specifications	5-liter container ISO 6743 DAJ Classification DIN 51506 VD-L Density at 20°C: 0.864 kg/l Appearance: clear, viscous liquid Color: light amber Viscosity at 40°C: 70 mm²/s Viscosity at 100°C: 10.8 mm²/s

	Viscosity index: 143 Flash point: 245°C Pour point: -35°C Storage stability: excellent
Warranty period	No warranty (consumable)
Capacity (ml)	5,000 ml
Capacity (l)	5 l
Tariff code	Tariff Normal (TN)
Warranty Procedure	NO
Consumable type	Lubricant



***Public price Exl. Tax : €70**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)