

COOLING SYSTEM TESTER

Reference : AC 1000



Item name	COOLING SYSTEM TESTER
EAN code	3700461410185
Intro	Allows circuit to be pressurized. Quick connect, fully sealed plugs. Range of plugs with latest models for all commercial vehicles and most HGVs. Allows immediate detection of circuit condition and cause of the leak (clamps, sleeves, cylinder head gasket...). Pump and plugs sold retail.
Text	Pump equipped with a pressure relief valve Plugs sold retail
Specifications	Procedure: A) Remove the radiator plug and clean the joint bearings (possible scale).For the test, attach the plug adapted to the type of nozzle to the radiator:1) Bayonet connectorChoose the size of the plug for the radiator you are testing.Screw the plug onto the bladed part.Fix the coupling's 2 metal blades onto the nozzle, turn the upper knob to make sure it is watertight2) Coupling screwScrew the plug onto the radiator and check that the rubber trim is correctly positioned.B) Attach the radiator tester to the plug using the quick connect located at the end of the pipe.C) Activate the pump until pressure is about 1bar. If the manometer needle stays still for about 1 minute, the circuit is working correctly. If the needle goes down, it means that there are leaks in the circuit, which can easily be located from where water is coming out. If the manometer goes down and no leak is found, the state of wear of the engine's cylinder head gasket needs to be checked.
Warranty period	2 years
Tariff code	Tariff Normal (TN)

Warranty ProcedureEASY

2
WARRANTY



TN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)