


LOW PRESSURE COUPLER FOR GAS R1234yf

Reference : SA 4054



Item name	LOW PRESSURE COUPLER FOR GAS R1234yf
Bar code	3700461456435
Introduction	<p>This specific 3/8" connection, compliant with SAE J639 standard, is dedicated to the refilling or leak detection of R1234YF air-conditioning gas.</p> <p>Thanks to its quick-release locking system, it can be easily connected to the vehicle for maintenance purposes.</p>
Text	R1234 gas is dedicated to new M1 and N1 class vehicles. In fact, the new European directive 2006/40/CE stipulates that in future, all refrigerants used must have a GWP (Global Warning Potential) of less than 150.
Warranty period	2 years
Tariff code	Tariff Normal (TN)
Warranty Procedure	EASY
Master item(s)	AC 1012 AIR CONDITIONING LEAK DETECTION KIT AC 1014 KIT AZOTE COMPLET DETECTION FUITES CLIMATISATION AC 1015 KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2) AC 1016 KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)



TN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)