

## Low pressure coupler for gas R1234yf

Reference : SA 4054



**Item name** Low pressure coupler for gas R1234yf

**Bar code** 3700461456435

**Introduction** This specific 3/8" connection, compliant with SAE J639 standard, is dedicated to the refilling or leak detection of R1234YF air-conditioning gas. Thanks to its quick-release locking system, it can be easily connected to the vehicle for maintenance purposes.

**Text** R1234 gas is dedicated to new M1 and N1 class vehicles. In fact, the new European directive 2006/40/CE stipulates that in future, all refrigerants used must have a GWP (Global Warning Potential) of less than 150.

**Warranty period** 2 years

**Tariff code** Tariff Normal (TN)

**Warranty Procedure** EASY

**Master item(s)** AC 1012 | AIR CONDITIONING LEAK DETECTION KIT  
AC 1014 | KIT AZOTE COMPLET DETECTION FUITES CLIMATISATION  
AC 1015 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)  
AC 1016 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)



TN

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)