

Low pressure coupler for gas R1234yf

Reference : SA 4054



Item name Low pressure coupler for gas R1234yf

Bar code 3700461456435

Introduction This specific 3/8" connection, compliant with SAE J639 standard, is dedicated to the refilling or leak detection of R1234YF air-conditioning gas. Thanks to its quick-release locking system, it can be easily connected to the vehicle for maintenance purposes.

Text R1234 gas is dedicated to new M1 and N1 class vehicles. In fact, the new European directive 2006/40/CE stipulates that in future, all refrigerants used must have a GWP (Global Warning Potential) of less than 150.

Warranty period 2 years

Tariff code Tariff Normal (TN)

Warranty Procedure EASY

Master item(s) AC 1012 | AIR CONDITIONING LEAK DETECTION KIT
AC 1014 | KIT AZOTE COMPLET DETECTION FUITES CLIMATISATION
AC 1015 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)
AC 1016 | KIT AZOTE HYDROGENE DETECTION FUITES CLIMATISATION (N2-H2)



TN

***Public price Exl. Tax : €52**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)