

ELECTRONIC STETHOSCOPE LEAK DETECTOR

Reference : AC 5028



Item name	ELECTRONIC STETHOSCOPE LEAK DETECTOR
Bar code	3700461456480
Introduction	<p>By simply touching the tip of the stethoscope's key, the noise emitted by the target part is transmitted to the headphones, enabling you to locate engine clicks, rolling noises, rattles, etc. during static checks.</p> <p>Its second function enables the detection of air leaks imperceptible to the human ear, by making audible the ultrasound emitted by an air stream.</p>
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- operates on 2 type 6f22 9V batteries or equivalent- frequency response: 36000Hz to 44000Hz- operating temperature: 0°C to 40°C- storage temperature: -10°C to 50°C- weight: amplifier 183g/transmitter 156g
Contents	<p>Contents :</p> <ul style="list-style-type: none">- amplifier 176x84x35mm- ultrasonic transmitter 170x84x36mm- headset- 250mm aluminum stethoscope probe- 270mm plastic amplification tube- carrying case with foam
Warranty period	2 years

More Powered by battery

Tariff code Tariff Normal (TN)

Warranty Procedure EASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)