Electronic stethoscope leak detector

Reference : AC 5028




Item name	Electronic stethoscope leak detector
Bar code	3700461456480
Introduction	By simply touching the tip of the stethoscope's key, the noise emitted by the target part is transmitted to the headphones, enabling you to locate engine clicks, rolling noises, rattles, etc. during static checks. Its second function enables the detection of air leaks imperceptible to the human ear, by making audible the ultrasound emitted by an air stream.
Specifications	Specifications: - Powered by 2 9V batteries (type 6F22 or equivalent) - Frequency response: 36,000 Hz to 44,000 Hz - Operating temperature: 0°C to 40°C - Storage temperature: -10°C to 50°C - Weight: amplifier 183 g / transmitter 156 g
Contents	Contents: - Amplifier, 176 x 84 x 35 mm - Ultrasonic transmitter, 170 x 84 x 36 mm - headphones - Aluminum stethoscope probe, 250 mm - plastic amplification tube, 270 mm - carrying case with foam padding
Warranty period	2 years

More Powered by battery

Tariff code Tariff Normal (TN)

Warranty Procedure EASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)