Air conditioning leak stop for R1234yf 30ml

Reference : CO 4070



Item name	Air conditioning leak stop for R1234yf 30ml
Bar code	3700461494802
Introduction	Closes micro-leaks in metal parts, hoses and seals. Saves time on hard-to-reach leaks.
Text	A product specially designed for the rapid repair of micro-leaks in air conditioning systems. Once introduced into the system, the sealant begins to circulate until the leak is located. When it escapes, the product reacts with the air, hardens, and permanently seals the micro-leak. Since the product contains no polymers, there is no risk of damage to circuit components and/or the air conditioning system. Unpressurized bottle containing no propellant: May only be used after the system has been evacuated using an a/c station. No gas is injected: no risk of overpressure or damage to the system (unlike syringes and aerosols). The bottle contains a liquid that is drawn in by the vacuum previously created in the system.
Product highlight	Cost-effective solution
Specifications	Specifications: Compatible with 1234YF Recommended for vehicles containing up to 350 ml of lubricant and 1.5 kg of refrigerant.

	The vehicle must be equipped with a 1234YF low-pressure fitting.
Warranty period	No warranty (consumable)
Capacity (ml)	30 ml
Capacity (l)	0.03 l
Tariff code	Tariff Normal (TN)
Warranty Procedure	NO
Consumable type	Additive



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)