

Air conditioning leak stop for R1234yf 30ml

Reference : CO 4070



Item name	Air conditioning leak stop for R1234yf 30ml
Bar code	3700461494802
Introduction	Closes micro-leaks in metal parts, hoses and seals. Saves time on hard-to-reach leaks.
Text	<p>A product specially designed for the rapid repair of micro-leaks in air conditioning systems.</p> <p>Once introduced into the system, the sealant begins to circulate until the leak is located. When it escapes, the product reacts with the air, hardens, and permanently seals the micro-leak.</p> <p>Since the product contains no polymers, there is no risk of damage to circuit components and/or the air conditioning unit.</p> <p>Unpressurized bottle containing no propellant: May only be used after the system has been evacuated using an a/c station.</p> <p>No gas is injected: no risk of overpressure or damage to the system (unlike syringes and aerosols).</p> <p>The bottle contains a liquid that is drawn in by the vacuum previously created in the system.</p>
Product highlight	Cost-effective solution
Specifications	Usable 1234YF Recommended for vehicles containing up to 350ml lubricant and 1.5kg coolant. Vehicle must be equipped with a 1234yf low-pressure fitting.

Warranty period No warranty (consumable)

Capacity (ml) 30 ml

Capacity (l) 0.03 l

Tariff code Tariff Normal (TN)

Warranty Procedure NO

Consumable type Additive

NO
WARRANTY



TN

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)