

## Air conditioning leak stop for R1234yf 30ml

Reference : CO 4070



<b>Item name</b>	Air conditioning leak stop for R1234yf 30ml
<b>Bar code</b>	3700461494802
<b>Introduction</b>	Closes micro-leaks in metal parts, hoses and seals. Saves time on hard-to-reach leaks.
<b>Text</b>	<p>A product specially designed for the rapid repair of micro-leaks in air conditioning systems.</p> <p>Once introduced into the system, the sealant begins to circulate until the leak is located. When it escapes, the product reacts with the air, hardens, and permanently seals the micro-leak.</p> <p>Since the product contains no polymers, there is no risk of damage to circuit components and/or the air conditioning unit.</p> <p>Unpressurized bottle containing no propellant: May only be used after the system has been evacuated using an a/c station.</p> <p>No gas is injected: no risk of overpressure or damage to the system (unlike syringes and aerosols).</p> <p>The bottle contains a liquid that is drawn in by the vacuum previously created in the system.</p>
<b>Product highlight</b>	Cost-effective solution
<b>Specifications</b>	Usable 1234YF Recommended for vehicles containing up to 350ml lubricant and 1.5kg coolant. Vehicle must be equipped with a 1234yf low-pressure fitting.

**Warranty period** No warranty (consumable)

**Capacity (ml)** 30 ml

**Capacity (l)** 0.03 l

**Tariff code** Tariff Normal (TN)

**Warranty Procedure** NO

**Consumable type** Additive

**NO**  
WARRANTY



TN

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)