

## Ultra-thin, variable-intensity rechargeable inspection lamps

Reference : OE 0145BL



<b>Item name</b>	Ultra-thin, variable-intensity rechargeable inspection lamps
<b>Bar code</b>	3700461495274
<b>Introduction</b>	The OE 0145BL is the versatile lighting solution for the budget-conscious. This inspection lamps from the B-Line range offers enhanced accessibility thanks to its slim profile, enabling it to illuminate congested areas without compromising workshop profitability.
<b>Text</b>	<p>Slim design: slim lighting head suitable for narrow passages and under-dash inspections.</p> <p>Variable intensity: Adjustable knob allows brightness to be set as required to optimize battery life.</p> <p>Swivel mount: magnetic base with swivel joint for quick positioning on metal chassis surfaces.</p> <p>COB LED technology: Wide beam for effective area lighting during routine maintenance operations.</p> <p>Rechargeable: powered by lithium battery via USB port, eliminating the cost of disposable batteries.</p>
<b>Product highlight</b>	Economical
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- ultra-slim head: 23x14mm</li><li>- COB LED illumination</li><li>- power: 10-600lm</li><li>- 6500 Kelvin</li><li>- dimmer (adjustable knob)</li></ul>

- runtime: 2 to 10h
- charge time: 4h
- battery type: Li-ion 3.7V - 2600mAh
- recharge: USB-micro USB cable
- 360° articulated hand lamp
- mounting: hook + magnet
- dimensions: 40x45x384mm
- weight: 175g

<b>Warranty period</b>	2 years
<b>Length (mm)</b>	45 mm
<b>Width</b>	40 mm
<b>Height</b>	384 mm
<b>Product weight (kg)</b>	175 kg
<b>Tariff code</b>	Tariff Normal (TN)
<b>Product range</b>	B-Line
<b>Warranty Procedure</b>	EASY
<b>Customer benefit</b>	Good value for money



**\*Public price Exl. Tax : €19**

\*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)