

(OS 5005)

#### **Specifications:**

- 32-position knob-type adjustment
- max. opening 70mm
- high-strength 58HRC steel
- standard DIN ISO 896



**€VAT Excl.** Instead of 38 €VAT Excl.\*



# 12 " ADJUSTABLE CRV WRENCH

(OS 0060)

#### **Specifications:**

- opening 34mm
- length 300mm
- CRV









TN





# 4 DRAWERS + 235 HGV TOOL DOOR ROLLER CABINET EG 4247

Cabinet "Made in France".

Wide and sturdy, it offers a larger work surface and a total load capacity of 900kg. Perforated on both sides, the cabinet is fully accessorizable (workshop bin, hand towel dispenser, etc...)

Its side lock located under the handle protects the key during handling.













































900 Kg load capacity













OS2100 : 1 x 7 pcs t-handle wrench insert torx t10-t40 OS2000: 1 x hex t-handle wrench insert 3-10mm (7 pcs)

OS1000 : 1 x screwdriver insert (8 pcs)

OS4100 : 1 x combination wrench insert 6-24mm (17 pcs) OS5399: 1 x hex. socket spanner insert 8-19mm (12 pcs) OS5499:1 x hex socket spanner insert 20-24mm (5 pcs)

OS3000 : 1 x 1/2" ratchet insert (23 pcs) OS5000:1x plier insert (4pcs)

OS6000:1 x special bit insert (43pcs)

OS4200:1x4 piece combination wrench insert 27-32mm

OS1100 : 1 x 7 pcs torx screwdriver insert t10-40

OS3200 : 1 x ratchet insert 1/4" (59pcs)
OS5200 : 1 x 4pcs circlip plier insert 7" inside-outside OS3450 : 1 x ratchet+hex socket set 3/4" d. (14 pcs)
OS3500 : 1 x hex impact socket kit 24-50mm 1" (9 pcs)

OS5024:1x24" aluminum claw wrench

EG0097 : 1 x 4 drawers + 1 door roller cabinet hgv

SA0881 : 1 x hammering insert OM0801:1 x 6 pin driver set with base

OM0803:1x automatic punch OM0160 : 1 x rivoir hammer composite handle 1000gr

OM0170 : 1 x dead blow hammer with interchangeable tip 32mm

OM0800: 1 x extra flat splitting chisel





TN RATCHET+HEX SOCKET SET 3/4" D. (14 PCS) 229 €VAT Excl. OS 3450 Contents: • OS3451: 3/4" hex socket 22mm • OS3452: 3/4" hex socket 24mm • OS3453: 3/4" hex socket 27mm • OS3454: 3/4" hex socket 30mm • OS3455: 3/4" hex socket 32mm • OS3456: 3/4" hex socket 36mm • OS3457: 3/4" hex socket 38mm • OS3458: 3/4" hex socket 41mm • OS3459: 3/4" hex socket 46mm • OS3460: 3/4" hex socket 50mm • OS3461: 3/4" ratchet • OS3462: 3/4" extension 200mm • OS3463: 3/4" extension 400mm OS3464: sliding T-handle 3/4" L.500mm





TN

RATCHET+8 HEX SOCKET SET 1" D. 46-80mm

OS 3550

- OS3551: 1" hex socket 46mm
- OS3552: 1" hex socket 50mm
- OS3553: 1" hex socket 55mm
- OS3554: 1" hex socket 60mm
- OS3555: 1" hex socket 65mm
- OS3556: 1" hex socket 70mm
- OS3557: 1" hex socket 75mm
- OS3558: 1" hex socket 80mm
- OS3559: ratchet
- OS3560: extension 200mm
- OS3561: extension 400mm
- OS3562: 1" sliding T-handle L.550mm







1"x3/4" REDUCER (OM 0043)

**€VAT Excl.** 

Instead of 22 €VAT Excl.\*



3/4"D. x 1/2"D. REDUCER OM 0044 2 €VAT Excl. Instead of14 €VAT Excl.\*

TN 1/2"D.x3/4" D. **INCREASER** OM 0045 **€VAT Excl.** Instead of 9 €VAT Excl.\*

TN 3/4"x1" **INCREASER** ( OM 0033 ) **€VAT Excl.** Instead of 14 €VAT Excl.\*

HGV 3/4" SOCKET SET XZN 16-18 TORX T70-T100 (6 PCS)

(OM 2332)



# 69 €VAT Excl. Instead of 95 €VAT Excl.\*







#### Contents:

- OS3431: 3/4" hex impact socket 26mm
- OS3432: 3/4" hex impact socket 27mm
- OS3433: 3/4" hex impact socket 29mm
- OS3434: 3/4" hex impact socket 30mm
- OS3435: 3/4" hex impact socket 32mm
- OS3436: 3/4" hex impact socket 35mm
- OS3437: 3/4" hex impact socket 36mm
- OS3438: 3/4" hex impact socket 38mm



HEX IMPACT SOCKET KIT 26-38mm 3/4" (8 PCS)

(OS 3400)



**€VAT Excl.** 

Instead of 99 €VAT Excl.\*



**€VAT Excl.** 

Instead of 158 €VAT Excl.\*


**DIN ISO 3129** 



# Contents:

- OS3401: impact socket 26mm
- OS3402: impact socket 27mm
- OS3403: impact socket 29mm • OS3404: impact socket 30mm
- OS3405: impact socket 32mm
- OS3406: impact socket 35mm
- OS3407: impact socket 36mm • OS3408: impact socket 38mm
- DIN ISO 2725-3





(OS 3430)



#### Contents:

- OS3431: 3/4" hex impact socket 26mm
- OS3432: 3/4" hex impact socket 27mm
- OS3433: 3/4" hex impact socket 29mm • OS3434: 3/4" hex impact socket 30mm
- OS3435: 3/4" hex impact socket 32mm
- OS3436: 3/4" hex impact socket 35mm
- OS3437: 3/4" hex impact socket 36mm • OS3438: 3/4" hex impact socket 38mm









# 1" LONG HEX IMPACT SOCKET SET 24-50mm (9 PCS)

OS 3530

#### Contents:

- OS3531: 1" long hex impact socket 24mm
- OS3532: 1" long hex impact socket 27mm
- OS3533: 1" long hex impact socket 30mm
- OS3534: 1" long hex impact socket 32mm
- OS3535: 1" long hex impact socket 35mm
  OS3536: 1" long hex impact socket 8mm
- OS3537: 1" long hex impact socket 41mm
- OS3538: 1" long hex impact socket 46mm
- OS3539: 1" long hex impact socket 50mm

**DIN ISO 3129** 









TN



# HEX IMPACT SOCKET KIT 24-50mm 1" (9 PCS)

OS 3500

#### Contents:

- OS3501: impact socket 24mm
- OS3502: impact socket 27mm
- OS3503: impact socket 30mm
- OS3504: impact socket 32mm
- OS3505: impact socket 35mm
- OS3506: impact socket 38mm
- OS3507: impact socket 41mm • OS3508: impact socket 46mm
- OS3509: impact socket 50mm

DIN ISO 2725-3





Instead of 174 €VAT Excl.\*



99 €VAT Excl.

Instead of 168 €VAT Excl.\*



# **(6)**

# TORQUE MULTIPLIER R1:58 4800Nm+6 SOCKETS + 2 ADAPTERS 1" HGV

(OM 4535)

Torquing and releasing

## Contents:

- torque multiplier R1:58 L.270mm
- extension L.255mm
- sockets 24-27-30-32-33-38mm, H.80mm 1" drive
- adapters 1" female-female and 3/4"male-1" female H.80mm







HGV AIR REEL Ø13mm 20m

OP 1628



299 €VAT Excl.

Instead of 389 €VAT Excl.\*

#### **Specifications:**

- epoxy powder coated steel brackets
- automatic hose stopping system
- hose Øint, 13mm
- max. pressure: 20bar
- connector 1/2"





TN

1" D. IMPACT WRENCH 2441Nm

(OP 1407)

# **Specifications:**

- max. torque: 2441Nm
- release torque: 2033Nm
- speed: 6,000rpm
- length: 467mm
- connection: 1/2"
- supply pressure: 6.2bar
- consumption: 2821/min
- net weight: 7.5kg







950 €VAT Excl.

Instead of 977 €VAT Excl.\*



TN

1" D. HGV IMPACT WRENCH 3390Nm

OP 1422

# **Specifications:**

- max. torque: 3390Nm
- speed: 5.000rpm
- length: 565mm
- connection: 1/2"
- supply pressure: 6.2bar
- consumption: 282I/min
- net weight: 11kg



**€VAT Excl.** 

Instead of 1099 €VAT Excl.\*







TN

# 1" D. ALUMINUM IMPACT WRENCH 2034Nm

OP 1409

## **Specifications:**

- speed: 5,500rpm drive: 1"
- max. torque: 2,034Nm
- working torque range: 271-1,627Nm
- connector: 3/8"
- average consumption: 1981/min
- recommended supply pressure: 6.2bar
- length: 228mm
- weight: 5kg









**€VAT Excl.** 

Instead of 559 €VAT Excl.\*





























# RECHARGEABLE ELECTRIC WHEEL LIFT 100 KG

OE 9100

Allows effortless lifting and lowering of LV, LCV, 4x4 and HGV wheels at vehicle height on the bridge. Facilitates wheel transport in the workshop. Low center of gravity increases stability.







#### **Specifications:**

- lifting capacity: 100kg wheel diameter 640-1000 mm
- max. lift height (at hub): 1450 mm
- up/down control integrated into handle
- lifting speed: 0.1m/s
- lifting system: motorized screw
- 4 wheels
- wheel anti-fall safety device
- mushroom-type emergency stop button
- rollers for easy rotation and positioning of wheel on hub
- LED indicators

Battery charge level

Max. load capacity exceeded

Emergency stop engaged

Screw motor temperature high

- batteries: 2 x 12V 18Ah ( 24V)
- charger: 220V-AC
- dimensions : L.900xl.1065xH.1450mm
- operates in temperatures ranging from -5 to +45°C







5690 €VAT Excl.



# TE

# HGV TIRE CHANGER 14"-26"

DM 8000

Truck, coach and farm machinery tyre changer for tubeless and tube-fitted tyres.

#### Features:

- cover diameter: 14 to 26 inches
- -maximum wheel diameter: 1600mm
- maximum width: 1000mm
- 1.5KW 380V/3PH-50AH hydraulic motor
- remote electric control
- operating pressure: 130-150bar
- noise < 75 dB
- power supply: 400V-50Hz
- weight: 561kg
- dimensions: 2100 x 1650 x 930mm
- delivered crate-mounted























ANTI-REBOUND HAMMER 4.5kg L.900mm Allows HGV wheels to be detached when they have adhered to the hub. - anti-rebound technology - plastic handle L.780mm - head dimensions: L .180xW.105xH.105 59 €VAT Excl. Instead of 69 €VAT Excl.\* CLAS 

WHITE WASHABLE MARKER FOR ALL **SURFACES** (EG 0021)

**€VAT Excl.** 



#### **Specifications:**

- UV resistant
- for all surfaces: metal, plastic, wood, glass, stone, foil...
- transparent body so you can immediately see how much paint is left
- VOC less than 0.6% (Volatile Organic Compounds)
- complies with standard ASTM D436 (non toxic)



TN

# TIRE RELEASER

### OP 1465

- Can be used on the vehicle
- Saves time
- Air regulator
- Handle exhaust
- Agricultural use

#### Specifications:

- travel: 80mm
- jaw opening: 68mm length: 380mm
- connection: 1/4"
- supply pressure: 6.2bar
- consumption: 1131/min









**€VAT Excl.** 

# HYDROPNEUMATIC BEAD BREAKER + PUMP/HOSE/ CONNECTOR

# DM 1204

# Bead breaker specifications:

- adapts to 17.5" to 60" wheels - max. opening.: 130mm

- air inlet, female threading 3/8"

# Pump specifications:

- 700bar
- aluminum body
- load limitor
- silent exhaust
- dimensions: L.255xW.135xH.185mm





Instead of 929 €VAT Excl.\*

TN

TN

TN

TN

JACK STANDS WITH SCREW 20T (x2)

(OM 3021)











749 €VAT Excl.

20T JACK STANDS WITH SCREW HIGH ELEVATION

(OM 3023)









819 €VAT Excl.

Instead of 945 €VAT Excl.

Instead of 329 €VAT Excl

Instead of 829 €VAT Excl.

PAIR OF HEIGHT ADJUSTABLE JACK STANDS 22T

OM 0684











**€VAT Excl.** 

**22T** 

**BOTTLE JACK 30T** 

OH 4530

#### **Specifications:**

- min. height: 275mm max. height: 440mm
- base: 169x153mm
- weight: 12.2kg









Robust & airtight thanks to the welded base **€VAT Excl.** 

Instead of 192 €VAT Excl.\*

**BOTTLE JACK 50T** 

(OH 4550)

#### **Specifications:**


- min. height: 265mm
- max. height: 425mm
- base: 210x176mm
- weight: 25kg











**€VAT Excl.** 

Instead of 265 €VAT Excl.\*

TN


# AIR HYDRAULIC JACK 10-22-40T

OH 9042N

Applications: Trucks, trailers, buses, agricultural machinery, civil engineering machinery.









# **EXTENSION:**



# **Specifications:**

- provides quick and effortless lifts
- safety overload system
- 3 stages: 40-22-10T
- equipped with a speed control descent system for enhanced security
- long T-handle allows you easily position your jack under the vehicle
- 3 positions: 90-45-0° with metal locking system
- tempered piston for high resistance

- h. min.: without extension 125mm/with extensions 256mm
- h. max.: without extension 276mm/with extensions 407mm
- length: 527mm
- width: 268mm
- extensions: 11-45-75mm
- air pressure: 9-12bar
- weight: 38,4kg







3-position handle: 90-45-0° metal locking system



T-handle: easy positioning under the vehicle



40T

# AIR HYDRAULIC JACK 15-30T

### (OH 3015N)

### **Specifications:**

- provides quick and effortless lifts
- safety overload system
- equipped with a speed control descent system for enhanced security
- 2 stages: 30-15T
- long T-handle allows you easily position your jack under the vehicle
   3 positions: 90-45-0° with metal locking system
- tempered piston for high resistance
- extensions: 45-75mm
- air pressure: 9-12bar
- weight: 38kg





















**€VAT Excl.** 

# AIR HYDRAULIC JACK 15-30-50T

# OH 5030N

# **Specifications:**

- provides quick and effortless lifts
- safety overload system
- equipped with a speed control descent system for enhanced security
- 3 stages: 50-30-15T
- long  $\overline{\text{T}}$ -handle allows you easily position your jack under the vehicle 3 positions: 90-45-0° with metal locking system
- h. mini: without extension 150mm/with extensions 270mm
- h. max: without extension 300mm/ with extensions 420mm
- tempered piston for high resistance
- extensions: 45-75mm
- air pressure: 9-12bar
- weight: 56kg



















**€VAT Excl.** 

### HIGH LIFT AIR HYDRAULIC JACK 30T

# OH 9032N

### **Specifications:**

- provides quick and effortless lifts
- safety overload system
- equipped with a speed control descent system for enhanced security
- long T-handle to ease jack positioning under vehicle
  3 positions: 90-45-0° with metal locking system
- tempered piston for high resistance
- min. height: without extension 360mm/with extensions 505mm
- max. height: without extension 627mm/with extensions 772mm
- length: 840mm
- width: 282mm
- extensions: 45-100mm
- air pressure: 9-12bar
- weight: 87kg



Applications: Civil engineering machinery, agricultural machinery, military machinery, trains.



















**€VAT Excl.** 



DRY AND WET VACUUM CLEANER 2x1000W + SPIRAL 4m

EG 1040











#### **Specifications:**

- stainless steel tank mounted on a 4-wheel dolly 2 motors of 1000W each
- 80l tank Ø420mm
- drain on 500mm tank
- pressure: 21kPa
- air flow: 108l/s
- sound level: 73dB
- power supply 230V 4m cable
- power: 2000W
- dimension (lengthxdepthxheight): 540x595x940mm





















**€VAT Excl.** 





65I HGV FLUID COLLECTION CONTAINER

(HU 0033)

For HGV ground draining. For engine oil, gearboxes..

- equipped with a breakwater grid and anti-drain back
- dimensions: 250x700x500mm



**€VAT Excl.** Instead of 299 €VAT Excl.\*





TN

65I HGV PIT COLLECTOR (HU 0114)

For engine oil, gearboxes...

- equipped with a breakwater grid and antidrain back
- drain valve underneath the tank
- waist width adjustment: 750mm mini, 1200mm maxi
- dimensions: 250x700x500mm



**€VAT Excl.** 





TN

# SPILL CONTAINMENT TRAY 480I 4 DRUMS (HU 0450)

#### **Specifications:**

- for 1 to 4 drums
- removable plastic slats
- compatible with forklifts and pallet trucks
- dimensions: L.1380xW.1290xH.480mm
- weight: 41kg













IVECO OIL FILTER WRENCH SET (3 PCS)

(HU 1992)

#### **Contents:**

- 91x15
- 96.5x15
- 108x15
- SA2069: 1/2"x3/8" reducer





**€VAT Excl.** 

TN

TN

MOBILE OIL DISTRIBUTION BARREL 180-220kg (HU 0613) **Contents:** HU0617: volumetric oil gun 1/2"HU0716: 180-220kg drum trolley • HU0619N: pneumatic oil pump + suction tube for 180-220kg drums

HU 0716



Instead of 36 €VAT ExcL\*





HU 0619N



# HGV AXLE DRAIN PAN

(HU 0035)

This pan has been designed to collect fluids from HGV axles. When removing a wheel shaft on an industrial vehicle, the oil in the reducers flows onto the rim. This pan has been designed to collect this oil.

- to be placed directly onto the wheel to collect the oil
- suitable for several rim sizes
- with pouring spout



19 €VAT Excl.

Instead of22 €VAT Excl.\*





TN

3 L

UNIVERSAL HGV HUB COVER REMOVAL TOOL 3/4"

(OM 0355)

#### Specifications:

- from Ø47mm to Ø145mm
- 3/4" D.
- 3 sets of pins for castle nuts





**€VAT Excl.** 



TN

6 PIN REAR HUB SOCKET LCV Ø67.5mm 3/4"

(OM 0001)

Specific socket to loosen the grooved nut of the rear wheel hub.

Renault : Movano ,Master VW : LT, Crafter

Nissan: Interstar Mercedes: Sprinter (with axles 741.130,131,413,414,416,

420,422,453,454,455,429)



**€VAT Excl.** 

Instead of 95 €VAT Excl.\*



More of hub sockets on clas.com



TN

# HEX MERCEDES HUB SOCKET Ø95mm 1"

OM 0301

Suitable for axles and trailers

**€VAT Excl.** 

Instead of 325 €VAT Excl.\*





# 8-SIDED FRONT HUB NUT SOCKET SCANIA Ø80mm 1"

OM 4480

Scania 124L, 144L, series 4<96

**Specifications:** 

drive 41mm



149 €VAT Excl.

Instead of 158 €VAT ExcL\*











TN

HGV HUB SOCKET SCANIA 1"

OM 0404











**329** €VAT Excl.

Instead of 359 €VAT Excl.\*





TN

UNIVERSAL HGV HUB PULLER (5 ARMS)

OM 3455

Features:

- max. opening diameter: 425mm
- for nuts M14 to M22
- force up to 30T





849 €VAT Excl.

Instead of 999 €VAT Excl.\*



TN

HALDEX® BRAKE LINKAGE ADJUSTER EXTRACTOR

OM 0390

Specifications:

- Ø78 mm



149 €VAT Excl.

Instead of 207 €VAT Excl.\*



TN

BPW BRAKE LINKAGE ADJUSTER EXTRACTOR

OM 0391

GSK/AGS

Specifications:

- Ø78 mm



129 €VAT Excl.

Instead of 200 €VAT Excl.\*





# CLAMPS FOR RILSAN PIPES Ø6-8-10-12-16mm

OM 0356

This tool is necessary for inserting notched connections into a rilsan/polyamide pipe as it keeps tire pipes (brake) or fuel pipes in good condition.

It can be used for  $\emptyset$ 6-8-10-12-16mm thanks to its adjustment knurled screw. Mainly used for heavy vehicles such as buses, coaches, trucks, tractors.



**€VAT Excl.** 







# DISK / HUB / BRAKE DRUMS SUPPORT


OH 8010

Specially designed to accommodate the entire hub (hub, disc and caliper) when changing bearings on trucks, buses and industrial vehicles. The assembly can be dismantled directly on the support, without effort, assisted by a winch for the removal of the bracket and disc. Limits the risk of accidents (back injury, fall of the stirrup on the feet...).



Instead of 3250 €VAT Excl.\*





#### **Specifications:**

- stroke: 200mm
- max winch load: 120kg
- 6 wheels including 2 braked castors

Flash to see the

- dimensions: 550x300x700mm
- weight: 49Kg

For optimal operation, the recommended methodology is (ex.: disk replacement):

- 1- use of the OH 8001 brake caliper support to maintain the initial position
- 2- use of the OH 8010 hub/caliper support to extract the assembly
- $\ensuremath{\mathrm{3-}}$  possible use of the OH 8012 disc extractor by cylinder in a case of force majeure





**?** €VAT Excl.

TN


# BRAKE SUPPORT AND CALIPERS WIDE BASE HGV

OH 8003

Specially designed for dismantling or changing brake calipers, bushings and drums on trucks, buses and industrial vehicles.

Reduces working time by up to 70%.

Limits the risk of accidents (back injury, fall of the stirrup on the feet... etc).





Flash to see the video!

#### **Specifications:**

- stroke: 200mm
- 4 swivelling wheels, 2 of which are braked
- dimensions : 550x300x700mm

4 positions caliper grip:

- 1' (12h)
- 2' (10h/2h)
- 3' (9h/3h)
- 4' (Specific with the offset rod for Mercedes).





# BRAKE DISC EXTRACTION CYLINDERS HW

OH 8013

Specially designed to separate the discs from the hub in record time when they are stuck by corrosion.

Reduces working time and secures the operation by avoiding the use of hammers, discers, cutting machines...

Limits the risk of accidents.





Flash to see the video!

#### **Specifications:**

- 2 independent 4T jacks on flexible hose L.1500mm
- min length: 84mm
- max length: 125mm
- stroke 41mm
- Ø piston: 32mm - foot pump max 700bar
- pump hoses length 220mm
- 4 wheels, 2 of which are braked swivel wheels
- dimensions: 470x300x500mm
- weight: 37kg







1590 €VAT Excl.

TN

# MINERAL/MULTIGRADE OIL ELECTRIC CLUTCH BLEEDER 5-20L 3.5bar

(HU 1108)

### **Specifications:**

- 220V power supply (5m cord) equipped with an on/off switch with pressure regulator 0-3.5bar

- pressure gauge for pressure control capacity 5 to 20 litres, allowing several operations
- flow rate: 40I/h
- interchangeable canister: ensures compatibility of the mineral/multigrade/pentosin liquid...
- flexible L.3.5m automatic triggering
- dimensions: 850x400x330mm
- weight: 22kg
- utilisation par une seule personne
- arrêt automatique
- test d'étanchéité

Recommended for HPS-2 gearboxes and clutches with secondary expansion tank (Mercedes Actros MP-II, ATEGO, AXOR...).









Control panel and digital controls



Universal piston with strainer







# HGV BATTERY/CATALYTIC CRANE

OH 8005

Specially designed for dismantling and handling batteries and catalyser on trucks, buses and industrial vehicles.








## **Specifications:**

- Max. load: 90kg
- 4 wheels including 2 brake swivelling wheels
- lifting height: 1890mm

Security chain Adjustable battery holder Battery strap







4350 €VAT Excl.

User price\*






TN


TN

# DPF ASSEMBLY/DISASSEMBLY **SCANIA**

(OM 7051)

For 5 and 6 cylinder engines (DC09-DC13)








**€VAT Excl.** Instead of 999 €VAT Excl.




# DOUBLE FAP SCANIA MOUNTING/ DISMOUNTING TOOL

(OM 7052)

2263984, 2765 198, 2765 199, 2765 200







990 €VAT Excl.



HYDRAULIC BALL JOINT PULLER KIT Ø30-34-40mm

OH 5020



**€VAT Excl.** Instead of 369 €VAT Excl.\*





TN

TN

6 PINS REAR SOCKET FOR VOLVO B12 ROLLERS Ø100mm 3/4"

OM 2556

Specially designed for the frame of the Volvo B12 buses and coaches.



**€VAT Excl.** Instead of 290 €VAT Excl.\*

#### Specifications:

- 6 lugs: 9.7mm long x 5mm thick, 115mm deep

For spherical plain bearings with part numbers : 20994563, 20739867, 70314325, 70321617 and equivalent



TN

3/4"FRONT WHEEL SHOCK ABSORBER SOCKET SCANIA 28x37mm

OM 0392



**€VAT Excl.** Instead of 34 €VAT Excl.\*

3/4" REAR WHEEL SHOCK ABSORBER SOCKET SCANIA 34x56mm

OM 0393



42 €VAT Excl.

Instead of 49 €VAT Excl.\*

# **Specifications:**

- length: 50mm socket outer
- diameter: 54 mm

3/4" REAR WHEEL SHOCK ABSORBER SOCKET SCANIA OUTER 34x46mm

( OM 0394 )



**€VAT Excl.** 

Instead of 41 €VAT Excl.\*

# **Specifications:**

- length: 50mm
- bushing outer diameter: 64mm



3/4" REAR WHEEL SHOCK ABSORBER SOCKET VOLVO 28x43mm

OM 0395

- length: 50 mm

- socket outer

diameter: 71mm



**€VAT Excl.** 

Instead of 45 €VAT Excl.\*

#### Specifications:

- length: 60mm
- socket outer diameter: 62 mm



# 20 LARGE Ø SOCKET SET

OM 9387

Contains 10 black long socket (L. 100mm) and 10 gold short socket (L. 30mm) with different diameters (70 to 88mm).









# HGV SILENT-BLOCK PULLER/ **INSTALLATION SET**

(OM 9381)

Allows the extraction and installation of split silent-blocks, which need to be compressed to be installed.

- support sockets (long and short) small diameter
- support sockets (long and short) large diameter
- 9 sets of half-rings + support ring
- silent-block compression vice
- extraction rod M20 + Nuts
- spacer for mechanical-hydraulic cylinder
- 1 step stop

Applications of half-rings + support ring:

- Ø56mm: Iveco Eurostar (Cabin)
- Ø58mm: Mercedes 3229B, 650,652 and Volvo
- Ø60mm: Mercedes and Iveco Eurostar (stabilizer), Renault Kerax,

Magnum, Premium (blade spring)

- Ø63mm: DAF
- Ø65mm: Mercedes Actros (stabilizer) and Atego
- Ø66mm: Iveco Eurostar (cabin)
- Ø68mm: Man (front), ROR, SAF
- Ø70mm: Man
- Ø75mm: Mercedes Actros (stabilizer)

1499 €VAT Excl.







### HYDRAULIC EXTRACTION SET

(OM 9385)



- SA9384: hydraulic cylinder 18T with 3/8" adapter
  SA9385: push spindle M10x1.5
- SA9386: push spindle M12x1.75
- SA9387: push spindle M14x1.5
- SA9388: push spindle M16x2.0
- 22 short bushes (40mm)
- 22 long bushes (110mm)
- plastic case
- SA4215: 1/4"-3/8" interface connector



**€VAT Excl.** 

Instead of 139 €VAT ExcL\*

TN

# **INSPECTION CREEPER 150kg**

(EG 0109)

#### **Specifications:**

- equipped with 2 tool holders
- carrying handle
- hydrocarbon-resistant material
- dimensions: 100x47x13cm
- Wheel Ø: 75mm
- high pressure washable
- reinforced wheel support





TN

# **HGV INDUCTION HEATER**

(OE 0900)

This tool allows to heat a part in a precise place, thus facilitating the unlocking of screws, nuts, bolts, rods, hubs (even rusty), lambda probes, ball bearings... It also makes it easy to remove stickers, remove glued door sticks or  $\ensuremath{\mathsf{HGV}}$  wheel nuts.

It is a real alternative to the torch or flame torch: its induction system allows to heat precisely and without flame a metallic (conductive) part without risk of deterioration of the surrounding nonconductive parts (glass, plastic, paint...)

In addition, the operator saves considerable time when using the tool.

#### **Specifications:**

- frequency: 18-60kHz
- power: 3.7kVA
- power regulator: 10-100%.
- control screen and timer
- LED illumination of the work area
- water-cooled
- dimensions: 240x200x440mm





Instead of 4499 €VAT Excl.\*





SA 0901 3L COOLING LIQUID







# **HYDROPNEUMATIC PRESS 100T**

OH 0910

### **Specifications:**

- hydraulic pump
- manual control or hydropneumatic pedal (dual pedal up and
- chrome plated piston with adjustment screw
- sliding cylinder with handle and positioning scale
- polycarbonate screen protection (5,5 cm) to protect the operator against possible splinters
- table height adjustable in 12 positions
- table raising/lowering assisted by winch
- table holding by 2 oversized pins
- large pressure gauge
- reversible V-shaped support block and plexiglass set included.

#### Option:

- OH0810: 100T puncher tools







100T PUNCHER TOOLS (OH 0810)

Accessory of OH 0910



149 €VAT Excl.




# HGV COOLING LINE TESTER SET

(AC 1002)

Allows simple and quick control by pressurizing the cooling circuits by connecting instead of the expansion tank cap.

- 5 metal plugs with quick coupling pressure regulator with relief valve
- control manometer 0 to 5bar
- vacuum filling kit
- 3 conical filling adapters
   filling pressure gauge -1 to Obar
   filling pipes with strainer











# **BUSES RADIATOR CRANE**

(OH 8006)


Specifically designed for dismantling radiators on buses.

# **Specifications:**

- lifting height: 1890mm
- 4 wheels including 2 braked castors







**3999** €VAT Excl.

Instead of 4590 €VAT Excl.\*





# BOOSTER 12-24V 6200A/3100A

(OE 5052)

#### **Specifications:**

- peak current (HPCA): 2540A (12V) / 1270A (24V) starting current (AC): 1580A (12V) / 790A (24V)
- cold start current (CCA): 1040-1100A (12V) / 520-550A (24V)
- capacity: 2x33Ah (12V) / 33Ah (24V)
- cables : 50mm², L.165cm
- integrated cigarette lighter socket
- charging time: 4-8h
- voltmeter digital charge indicator
- battery : AGM
- weight : 29kg
- dimensions : 410x280x550mm





Mobile and powerful

















# **HGV CLUTCH ALIGNMENT TOOL**

(OM 0621)

For accurate mouting, positioning and centric on single and double disc clutches.

#### Contents:

- 1 expanding guide from 36 to 48mm1 expanding guide from 42 to 52mm
- 4 centering valves Ø20-25-27-30mm









LCV/HEAVY WEIGHTS MOBILE GAS VACUUM 1m Ø150mm

(AG 0025)

#### **Specifications:**

- galvanized steel structure
- platform mounted on 4 swivel wheels
- epoxy paint (grey RAL 7040)
- suction hose: 1m
- discharge Ø125mm length 10m
- max. temperature: 200°C
- power supply: 230V Mono
- motor power: 1.5hp, 1.1KW, 50HZ, 4.2A
- max flow: 1200m3/h
- noise level: 72dB
- on/off switch
- stainless steel exhaust nozzle Ø 230mm
- weight: 61 kg

Numerous options available on request.

















2750 €VAT Excl.





TE

# MECHANICAL EXTRACTOR REEL GAS **HGV**

(EG 0424)

### **Specifications:**

- cast aluminium fan
- 8m anti-crush rubber hose Ø150mm-200°C
- automatic winder with ratchet stop
- supplied without extraction duct
- discharge: Ø160mm
- 400V three-phase power supply
- -motor power: 1.0hp, 0.75KW, 50 HZ, 1.7A
- max flow: +/- 1500m3/h noise level +/-70dB
- switch included
- polycarbonate flanges
- weight: 83kg

























TE

# EXHAUST GAS ON ROLL HEAVY WEIGHTS 10m Ø150mm

AG 0015

Specially designed for exhaust gas suction for HGV workshops.

# **Specifications:**

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 10m Ø150mm pipe (-40° to +200°) in high-temperature EPDM vulcanized fabric on both sides
- discharge: Ø 160mm
- power supply: 400 Tri
- motor power: 1.0hp, 0.75KW, 50HZ, 1.7A
- max flow: 1000m3/h
- noise level: 68dB
- thermally protected switch
- metal flanges
- reel equipped with ratchet, end-stop and anti-slip system
- exhaust nozzle equipped with anti-intrusion grid, vice grip, gas suction shut-off flap and access for opacimeter probe
- weight: 73kg

Numerous options available on request.















